

REMOVAL OF HEAVY METALS FROM
INDUSTRIAL WASTEWATER USING FRUITS
PEEL AS A LOW-COST BIO-ADSORBENT

NURUL FATINAH AFIQAH
BINTI BAHARUDIN

B. ENG (HONS.) CIVIL ENGINEERING

UNIVERSITI MALAYSIA PAHANG



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : NURUL FATINAH AFIQAH BINTI BAHARUDIN

ID Number : AA15295

Date : 31 MAY 2019

REMOVAL OF HEAVY METALS FROM INDUSTRIAL WASTEWATER USING
FRUITS PEEL AS A LOW-COST BIO-ADSORBENT

NURUL FATINAH AFIQAH BINTI BAHARUDIN

Thesis submitted in partial fulfillment of the requirements
for the award of the
B. Eng (Hons.) Civil Engineering

Faculty of Civil Engineering & Earth Resources
UNIVERSITI MALAYSIA PAHANG

MAY 2019

ACKNOWLEDGEMENTS

All praise is due to Allah, Lord of the Worlds, for His showers of blessings throughout the journey of completing my research work from the moment I started my research upon completion. Foremost, I would like to express my sincere gratitude to my supervisor Mrs. Suryati Binti Sulaiman for the guidance, help, and support. Thank you for all the advice, ideas, moral support and patience in guiding me during the period of research and thesis writing.

I acknowledge my sincere indebtedness and gratitude to my parents, Baharudin Basri and Kamisah Osman and the rest of my family members for their love, dream, and sacrifice throughout my life. I cannot find the appropriate words that could properly describe my appreciation for their devotion, support, and faith in my ability to attain my goals.

My sincere thanks also go to all my lab mates and staff of the Environmental Laboratory UMP, Mr. Qari, Mrs. Azimah and Mr. Suhaimi, who helped me in conducting experiment until I achieve the objective of my study. Many special thanks go to a member of the environmental group for their excellent co-operation, inspirations, and supports during this study.

Special thanks to my friends that keep supporting and help me throughout this project. I will not be able to keep myself strong without their nice words and advice. I am grateful and happy to have good friends around me which were crucial for the successful completion of this study.

ABSTRAK

Untuk menghilangkan logam berat dari air kumbahan industri, proses rawatan konvensional yang biasanya digunakan mempunyai beberapa kelemahan. Kaedah penyerapan adalah salah satu proses alternatif untuk menghilangkan logam berat. Walau bagaimanapun, harga bagi penggunaan “activated carbon” sebagai penyerap adalah mahal. Salah satu penyelesaian yang disyorkan adalah dengan menggunakan kulit buah sebagai bio-penyerapan. Kajian ini bertujuan untuk menentukan kapasiti optimum kulit pisang, mangga dan oren sebagai bio-penjerapan dalam merawat air kumbahan industri. Selain itu, ia juga bertujuan untuk membandingkan kesan dari segi masa, pH awal dan suhu dalam penyingkiran logam berat. Selain itu, kajian ini akan menganalisis kajian penjerapan dari segi “dosage”, tahap pH, suhu dan masa. “Langmuir adsorption model” disahkan dengan cara plot linear C_e / q_e terhadap C_e . Hasilnya menunjukkan bahawa kapasiti optimum penyerapan untuk penyerap oren, pisang dan mangga mengurai sekitar 1.2 gram, 0.8 gram dan 1.6 gram dengan tahap pH terbaik 4 untuk oren dan mangga manakala pH 2 untuk pisang. Suhu tidak mempengaruhi kecekapan penjerapan dalam lingkungan 29°C hingga 49°C dan untuk kesan masa, penyerap menyerap dengan cepat pada 20 minit pertama dan secara beransur-ansur meningkat dan kekal stabil selepas beberapa minit. Kajian ini mendedahkan bahawa kulit buah-buahan terbaik yang boleh digunakan sebagai penyerap adalah kulit oren kerana ia dapat menyerap banyak ion plumbum berbanding dengan dua buah yang lain.

ABSTRACT

In order to remove heavy metal from industrial wastewater, the conventional treatment processes that usually been use have several disadvantages. Adsorption method is the alternative process to remove heavy metal. However, the cost of using activated carbon as an adsorbent is expensive. One of the recommended solutions is to use fruits peel as a bio-adsorbent. This study aims to determine the optimum capacity of banana, mango and orange peel as bio-adsorption in treating industrial wastewater. Besides that, it also aims to compare the effect of contact time, initial pH and temperature in the removal of heavy metals. Other than that, this study will analyze the batch adsorption study base on dosage, pH level, temperature and contact time. Langmuir adsorption model was used which is confirmed by a linear plot of C_e/q_e against C_e . The results showed that optimum adsorption capacity for orange, banana and mango peel adsorbent is around 1.2gram, 0.8gram and 1.6gram respectively with the best pH level of 4 for orange and mango meanwhile pH 2 for banana. The temperature does not influence the efficiency of adsorption in the range of 29°C until 49°C and for the effect of contact time, the adsorbent absorbs rapidly at the first 20 min and gradually increase and remained stable after a few minutes. This study revealed that the best fruits peel that can be used as an adsorbent is orange peel as it can absorb many lead ions compare with the other two fruits peel.

TABLE OF CONTENT

DECLARATION

TITLE PAGE

ACKNOWLEDGEMENTS **ii**

ABSTRAK **iii**

ABSTRACT **iv**

TABLE OF CONTENT **v**

LIST OF TABLES **viii**

LIST OF FIGURES **ix**

LIST OF SYMBOLS **xi**

LIST OF ABBREVIATIONS **xii**

CHAPTER 1 INTRODUCTION **1**

1.1 Introduction 1

1.2 Problem Statement 3

1.3 The objective of the Study 4

1.4 Scope of the Study 4

1.5 Significance of the Study 5

CHAPTER 2 LITERATURE REVIEW **6**

2.1 Introduction 6

2.2 Wastewater 7

2.2.1 Industry Wastewater 7

2.3 Water Quality Parameter 8

2.4	Heavy Metal	9
2.4.1	Cooper	10
2.4.2	Lead	11
2.5	Treatment Methods	12
2.5.1	Adsorption Process	13
2.6	Bio-adsorbent	14
2.6.1	Orange Peel	15
2.6.2	Banana Peel	15
2.6.3	Mango peel	16
CHAPTER 3 METHODOLOGY		17
3.1	Introduction	17
3.2	Materials and Equipment	17
3.2.1	Wastewater Composition	17
3.2.2	Bio-adsorbent	19
3.2.3	Chemical and Reagents	20
3.2.4	Equipment	23
3.3	Analytical Method	24
3.3.1	Batch Adsorption Studies	24
3.3.2	Adsorption Isotherms	25
3.4	Experimental Procedures	25
3.4.1	Preparation of Adsorbent	25
3.4.2	Preparation of Wastewater	26
3.4.3	Bio-adsorption Studies	27

CHAPTER 4 RESULTS AND DISCUSSION	29
4.1 Introduction	29
4.2 Batch Adsorption Studies	29
4.2.1 Adsorption in term of dosage	29
4.2.2 Adsorption in term of pH	32
4.2.3 Adsorption in term of temperature	34
4.2.4 Adsorption in term of contact time	36
4.3 Adsorption Isotherms	38
4.3.1 Adsorption in term of dosage	38
4.3.2 Adsorption in term of pH level	41
4.3.3 Adsorption in term of temperature	43
4.3.4 Adsorption in term of contact time	46
CHAPTER 5 CONCLUSION	49
5.1 Conclusion	49
5.2 Recommendation	50
REFERENCES	51
APPENDIX A Template of Data collection	53

LIST OF TABLES

Table 2.1	Water pollutants by the industrial sector (Shi, 2017)	8
Table 3.1	List of equipment	23
Table 4.1	Result of Orange adsorbent	30
Table 4.2	Result of Banana adsorbent	30
Table 4.3	Result of Mango adsorbent	30
Table 4.4	Result of Orange adsorbent	32
Table 4.5	Result of Banana adsorbent	32
Table 4.6	Result of Mango adsorbent	33
Table 4.7	Result of Orange adsorbent	34
Table 4.8	Result of Banana adsorbent	34
Table 4.9	Result of Mango adsorbent	35
Table 4.10	Result of Orange adsorbent	36
Table 4.11	Result of Banana adsorbent	36
Table 4.12	Result of Mango adsorbent	37
Table 4.13	Result of Orange adsorbent	38
Table 4.14	Result of Banana adsorbent	39
Table 4.15	Result of Mango adsorbent	39
Table 4.16	Result of Orange adsorbent	41
Table 4.17	Result of Banana adsorbent	41
Table 4.18	Result of Mango adsorbent	42
Table 4.19	Result of Orange adsorbent	43
Table 4.20	Result of Banana adsorbent	44
Table 4.21	Result of Mango adsorbent	44
Table 4.22	Result of Orange adsorbent	46
Table 4.23	Result of Banana adsorbent	47
. Table 4.24	Result of Mango adsorbent	47

LIST OF FIGURES

Figure 2.1	Cooper metal	10
Figure 2.2	Lead metal	11
Figure 2.3	Chemical precipitation	12
Figure 2.4	Ion exchange	12
Figure 2.5	Adsorption process	13
Figure 2.6	Adsorption phase	14
Figure 2.7	Orange peel	15
Figure 2.8	Banana peel	16
Figure 2.9	Mango peel	16
Figure 3.2	Sample of wastewater	17
Figure 3.1	Study flowchart	18
Figure 3.3	Orange Adsorbent	19
Figure 3.4	Banana Adsorbent	19
Figure 3.5	Mango Adsorbent	20
Figure 3.6	Nitric Acid (HNO_3)	20
Figure 3.7	pH Meter	21
Figure 3.8	Cooper Standard	22
Figure 3.9	Lead Standard	22
Figure 3.10	AAS equipment	24
Figure 3.11	Step of adsorbent preparation (a) washed the fruit's peel, (b) dried the fruits peel in the oven, (c) crush the fruits peel and (d) sieve the adsorbent	26
Figure 3.12	Preservation of wastewater	27
Figure 3.13	Adsorption test	28
Figure 3.14	Checking heavy metal using AAS	28
Figure 4.1	The percentages of adsorption against adsorbent dose	31
Figure 4.2	Result between the percentages of adsorption against pH level	33
Figure 4.3	Graph between the percentages of adsorption against temperature	35
Figure 4.4	Profile of adsorption efficiency at different contact time	37
Figure 4.5	Langmuir adsorption isotherm for orange	38
Figure 4.6	Langmuir adsorption isotherm for banana	39
Figure 4.7	Langmuir adsorption isotherm for mango	40
Figure 4.8	Langmuir adsorption isotherm for orange	41
Figure 4.9	Langmuir adsorption isotherm for banana	42

Figure 4.10	Langmuir adsorption isotherm for mango	42
Figure 4.11	Langmuir adsorption isotherm for orange	43
Figure 4.12	Langmuir adsorption isotherm for banana	44
Figure 4.13	Langmuir adsorption isotherm for mango	45
Figure 4.14	Langmuir adsorption isotherm for orange	46
Figure 4.15	Langmuir adsorption isotherm for banana	47
Figure 4.16	Langmuir adsorption isotherm for mango	48

LIST OF SYMBOLS

mg/l	Milligram per litre
°c	Degree Celsius
ppm	Parts per million
mol/l	Molar concentration per litre
mm	Millimetre
L/mg	Litre per milligram
mg/g	Milligram per gram
g	Gram
q_e	Amount of adsorption at equilibrium
C_o	Initial concentration
C_e	Equilibrium concentration
V	Volume of solution
X	Weight of adsorbent
b	Constant related to the energy
Q_o	Mass of adsorbed solute required to saturate a unit mass of adsorbent
R_L	Equilibrium parameter

LIST OF ABBREVIATIONS

Cu	Copper
Pb	Lead
Cd	Cadmium
Hg	Mercury
As	Arsenic
Cr	Chromium
Se	Selenium
Ni	Nickel
Ag	Silver
Zn	Zinc
Fe	Iron
AAS	Atomic adsorption spectrophotometry
BOD	Biochemical oxygen demand
COD	Chemical oxygen demand
WHO	World Health Organization
DOE	Department of Environment
-OH	Hydroxide
HNO ₃	Nitric acid
NaOH	Sodium hydroxide

CHAPTER 1

INTRODUCTION

1.1 Introduction

Water is valuable natural resources to human, all living things and a healthy environment. Human needs water to complete their routine in daily life. Water also has been used in industrial in order to make sure their plants are running well instead as the main resource for drinking. Water is a transparent fluid which produces the streams, lakes, oceans, and rain, and is the principal constituent of the fluids of organisms. As a chemical compound, a water molecule contains one oxygen and hydrogen atoms that are related through covalent bonds. All living things will not survive without water for a long term and same goes to the industry which is it cannot be functional without existing of water. Besides, water plays an important role in the population growth and rapid development as the clean water resources needed as the pre-requisite in the existing of remain population.

Nowadays, because of the rapid growth of the industrial sector, the productions of heavy metal wastes into the water have been increasing day by day. Heavy metal pollution in the environment is one of the serious pollutions that occur globally. In recent years, ecological and global public health concern associated with environmental by these heavy metals has increased. The discharge of heavy metals from various sources especially from industry and agricultural into the aquatic ecosystem can accumulate in living tissues causing various disease and disorders. The industrial effluents which contain different derivatives of heavy metal such as copper, lead, cadmium, mercury, arsenic, chromium, selenium, nickel, silver, and zinc are continuously discharging to the ecosystem and producing a significant toxic on the aquatic environment. These heavy metals will persist in the environment since they

cannot be degraded and finally reach to the human food chain and result in the health problems.

Among these heavy metals, lead and copper is the most common pollutants found in the industrial effluents (Kahraman & Erdemoglu, 2008). The excess for lead in the water poses severe health risks to humans such as cancer, reproductive system disorders, high blood pressure, heart disease and skin disease (Abbaszadeh et al., 2018). Besides that, although copper is an essential present element the high level of it can cause harmful effects to human health (Kahraman & Erdemoglu, 2008). In most of the wastewaters, the concentration of heavy metals present is much larger than the safe permission limit. Therefore, the removal of heavy metal is one of the most important environmental issues that need to be solved.

In order to remove the heavy metal, there are several treatment processes that can be done such as chemical precipitation, membrane filtration, ion exchange, adsorption, co-precipitation and extraction (Bhatnagar et al., 2010). Among these treatment processes, the adsorption method is the most effective method to remove the heavy metals as it offers some benefit such as easy to operate, do not require any high skilled labour, environmentally safe and the process is non-destructive so that contaminants can be separated and recycled (Ahmad & Danish, 2018). The main parameter for doing adsorption is the adsorbent for removal and extraction purpose. The adsorbent that has been used is usually activated carbon as it has known for the effectiveness in removing heavy metal especially copper and lead from wastewater. Recently the researches have been made to use the nature adsorbent to replace the activated carbon.

1.2 Problem Statement

In order to remove the heavy metal, several treatment processes can be done such as chemical precipitation, membrane filtration, ion exchange, co-precipitation, and extraction. However, these methods proved either inefficient or expensive in case of low concentration (1-100mg/l) of heavy metals prevailing in the environment and generate a huge amount of sludge which is difficult to be disposed of (Ahmad & Danish, 2018). Other than that, most of these methods are not suitable for a small-scale industry which affects the operational cost and excess amount of chemical usage

Because of that, adsorption method is been select as an alternative to removing the heavy metal due to their low cost, easy to operate, do not require any high skilled labour, environmentally safe and the process is non-destructive so that contaminants can be separated and recycled. However, the use of commercial activated carbon as an adsorbent makes the adsorption process expensive. The high demand for activated carbons in other advanced application make in increasing their cost.

Therefore, in order to decrease the cost of the adsorbent, many kinds of research have been conducted to find the low cost of adsorbent with the high metal binding which is by using agricultural waste. The agricultural waste has been developed as it shows some advantages as it was cheap, readily available, low-cost, simple to use and environment friendliness. The agricultural waste such as chitosan, chitin, sugarcane bagasse, apple and orange juice residue, banana, wheat straw, rice husk, tea waste has been investigated as bio-sorbent for removal of heavy metals (Ahmad & Danish, 2018). Fruits peel is one of the agricultural wastes that can be used as bio-adsorbent. While these materials are considered wastes with a low or no economic value, and usually present removal and disposal, this transformation toward bio-adsorbent material add economic value and also help on reducing the disposal costs (Romero-Cano, 2016).

In this study, banana, mango, and orange peel have been select in order to produce bio-adsorbent though environment-friendly process. The residues of this fruit can be processed and convert it to be adsorbents because it's had a large surface area, high swelling capacities, and excellent mechanical strength and is convenient to use and

REFERENCES

- A.G.El Said, A. M. G. (2012). Volume 7, Issue 3, Spring2012. *Potential Application of Orange Peel (OP) as an Eco-Friendly Adsorbent for Textile Dyeing Effluents*, 7(3), 1–13.
- Abbaszadeh, S., Nodeh, H. R., & Alwi, S. R. W. (2018). Bio-adsorbent derived from papaya peel waste and magnetic nanoparticles fabricated for lead determination. In *Pure and Applied Chemistry* (Vol. 90, pp. 79–92).
- Ahmad, T., & Danish, M. (2018). Prospects of banana waste utilization in wastewater treatment: A review. *Journal of Environmental Management*, 206, 330–348.
- Akpor, O. B. (2014). Heavy Metal Pollutants in Wastewater Effluents: Sources, Effects, and Remediation. *Advances in Bioscience and Bioengineering*, 2(4), 37.
- Arbabi, M., & Golshani, N. (2016). Removal of copper ions Cu (II) from industrial wastewater: A review of removal methods. *International Journal of Epidemiologic Research*, 3(3), 283–293. Retrieved from
- Arbabi, M., Hemati, S., & Amiri, M. (2015). Removal of lead ions from industrial wastewater: A review of Removal methods. *International Journal of Epidemiologic Research*, 2(2), 105–109.
- Bhatnagar, A., Minocha, A. K., & Sillanpää, M. (2010). Adsorptive removal of cobalt from aqueous solution by utilizing lemon peel as biosorbent. *Biochemical Engineering Journal*, 48(2), 181–186.
- Fauzi Abdullah, M., Jawad, A. H., Hanani Mamat, N. F., & Ismail, K. (2016). Adsorption of methylene blue onto acid-treated mango peels: Kinetic, equilibrium, and thermodynamics. *Desalination and Water Treatment*, 59(January), 210–219.
- Jena, S., & Sahoo, R. K. (2017). Removal of Pb (II) from Aqueous Solution Using Fruits Peel as a Low-Cost Adsorbent. *International Journal of Science, Engineering and Technology*, 5(1), 5–13.
- Kahraman, S., & Erdemoglu, S. (2008). Use of various agricultural wastes for the removal of heavy metal ions Sibel Kahraman * Nukhet Dogan Sema Erdemoglu, (October).
- Odlare, M. (2014). *Introductory Chapter for Water Resources. Reference Module in Earth Systems and Environmental Sciences*. Elsevier Inc.

- Romero-Cano, L. A. (2016). Preparation of orange peels by instant controlled pressure drop and chemical modification for its use as biosorbent of organic preparation of orange peels drop and chemical modification for its use as biosorbent of, *15*(2), 481–491.
- Science, W., & Juang, R. (2014). Adsorption of Heavy Metals From Water Using Banana and Orange Peels Adsorption of heavy metals from water using banana and orange peels, (January 2003).
- Shi, H. (2017). Industrial wastewater. *Industrial Wastewater-Types, Amount and Effects, I*.
- Taylor, P., Gupta, V. K., Carrott, P. J. M., & Carrott, M. M. L. R. (2012). Critical Reviews in Environmental Science and Technology Low-Cost Adsorbents : Growing Approach to Wastewater Treatment — a Review Low-Cost Adsorbents : Growing Approach to Wastewater Treatment — a Review, (November 2012), 37–41.
- Tun, U., Onn, H., & Pahat, B. (2017). An Overview of Fruit Waste as Sustainable Adsorbent for heavy metal Removal and Azizul-Rahman M-F-H ~. *An Overview of Fruit Waste as Sustainable Adsorbent for Heavy Metal Removal*.
- Wachirasiri, P., Julakarangka, S., & Wanlapa, S. (2009). The effects of banana peel preparations on the properties of banana peel dietary fiber concentrate. *Songklanakarin Journal of Science and Technology*, *31*(6), 605–611.